

BEAUFORT
Diesel Cookstove**Model #00-BEA**

WEIGHT	360 LBS
HEIGHT	36"
WIDTH	35.5"
DEPTH	28.5"
FLUE SIZE	5" DIAMETER
FUEL CONSUMPTION	1.94 gal/24 hr - Low 6.4 gal / 24hr - High
HEAT OUTPUT	7,750 BTU - 32,000 BTU
WATER COIL	Optional Single or Double Turn
COMBUSTION ASSIST FAN	Standard 12V DC
INSTALL CONSIDERATIONS	Install facing bow or stern or retrofit valve.

Product Includes:

searail, splashback, 2 sets pot holders (fiddles), oven rack, thermometer, separate remote mounted speed control (12v, 24v or 32v), hold down strap, drip pan, flame view window and utility drawer.

Options:

- Single or Double turn hot water coil installations.
- fan voltage options;
- valve calibration for diesel (standard), stove oil or kerosene,

The BEAUFORT diesel cookstove is our largest model of oil cookstove. It features the high output 7" Stainless Steel burner. This stove is great for producing heat for larger boats, for cooking and for producing hot water with the optional water coil heat exchangers. This stove uses 5 inch diameter flue components. Use with Dickinson stainless steel flue pipe, 45 degree elbows, barometric dampers, deck-fittings and exhaust caps. A Heatex hot air heat exchanger is also available. We recommend the use of a barometric damper on flues greater than 6 feet in height.

Installation guidelines require a minimum 4 foot flue rise and heat clearances of more than 6 inches or a min of 2 inches to an insulated surface. See the owner's manual for details. A utility drawer is included, perfect for pots and pans.

Standard fuel metering for this stove is the Dickinson 5D valve for diesel. Stove Oil (5S) and Kerosene (5K) are also available as options or add ons. A 12vdc assist fan is standard for start up or high fire burn. 24v and 32v available as options or add ons.